



See notes 2 & 3

Mortar bed 10-20mm in accordance with SHW series 2400, table 24/1 with mortar designation (i)

CEMENT	LIME*	SAND
1	0-1/4	3

*Lime is optional.

Notes :-

1. Loading
Cover to be class B125 for pedestrian, forecourts
Cover to be class C250 for factories and industrial
Cover to be class D400 for access road
2. Contractor to use only the approved type of cover by each operation
3. Covers to be in accordance with BS EN 10025 and are kite marked. Min. wall thickness is 6mm steel.
4. Size of clear opening to match existing. For new chambers refer to the specification
5. Finish to be galvanised coating in accordance with BS EN Iso 1461



SCHEME
STANDARD DETAIL SHEETS



DRAWING
PAVIOR INFILL
COVER AND FRAME
SINGLE LEAF

This detail is controlled by Birmingham City Council. Email - Transport.Projects@Birmingham.gov.uk

2013	C	DETAILS & FRAME AMENDED	DH	PP
2004	B	NOTES AMENDED	-	AJC
2002	A	BORDER & TITLE AMENDED	-	AJC
2000	-	ORIGINAL DRAWING CREATED	SRE	AJC
DATE	REV.	REVISIONS	DRN	PM
DRAWN	DESIGNER	PM	PP	REVISION
DH	TE	03/12/13	03/12/13	C
DRAWING STATUS	GENERAL			
DWG. No	HW/5.04			
SCALE	1:10			

